## SERVOMEX OxyDetect - General Purpose Locations

# NON-DEPLETING PARAMAGNETIC SAFE AREA/GENERAL PURPOSE OXYGEN MONITOR DESIGNED FOR LIFE SAFETY APPLICATIONS



### SERVOMEX OxyDetect

The SERVOMEX OxyDetect is a breakthrough in life safety: a general purpose/safe area (O<sub>2</sub>) monitor that accurately monitors oxygen levels without the sensor deterioration that affects traditional electrochemical sensors used in competitor detectors. Designed for use in life critical applications, the OxyDetect utilizes the Hummingbird Paracube® Modus Paramagnetic sensor, whose industryleading levels of linearity, accuracy and reliability have ensured its use as a trusted O<sub>2</sub> sensor for the OEM medical market. The OxyDetect demonstrates several advantages over traditional technologies, ensuring an unprecedented level of safety and performance as well as a lower cost of lifetime ownership.

As well as significantly reducing the cost of ownership, the OxyDetect utilizes advanced microprocessor-based diagnostics that are safe, reliable and easy to access via a simple front panel digital interface.

#### **APPLICATIONS**

- Pharmaceutical plants
  Helium production and storage
  Semiconductor facilities
  Industrial Gas plants
  ASU plants
  Laboratories & Universities
  Welding facilities and workshops
   Bottling plants and storage
- Suitable for indoor use for temperatures ranging from 41°F to 113°F (5°C to 45°C)
- Light wall-mountable design for easy installation

### **EASY TO USE**

or SPCO relay

- Easy to use digital interface
- Fault alarm via mA jam to 0mA
- Simple integration via isolated 4-20mA output with linear measurement

Output range of 0-25% O<sub>2</sub>

Alarm 2, Fault

Ethernet, Modbus TCP

3 x SPCO relays, Alarm 1,

#### LOW COST OF OWNERSHIP

- Non-depleting Paramagnetic design delivers long life sensor without measurement deterioration
- Eliminates costs associated with regular replacement of electrochemical cells
- Exceptional measurement stability eliminates need for frequent calibration
- Not affected by sterile area cleaning agents

#### UNRIVALLED PERFORMANCE

- Innovative life-safety performance from the industry leader in Paramagnetic sensing technology
- Uses advanced microprocessorbased diagnostics that are safe, reliable and easy to access

#### **BENCHMARK COMPLIANCE**

IP65

SERVOMEX.COM

■ IEC 61010-1

CE, in compliance with Low Voltage, EMC and applicable directives

Learn more about the OxyDetect VISIT SERVOMEX.COM



### PRODUCT DATA: OxyDetect - General Purpose Locations

SAMPLE FOR MEASUREMENT	s	
Sample gas	Ambient air	
Sample pressure	Atmospheric	
MEASUREMENT PERFORMANCE		
Measurement	0 to 25% Oxygen	
Accuracy	±0.2% Oxygen	
Zero drift	<±0.2% Oxygen per month*	
Zero temp coefficient	<+/-0.5% O2 per 10°C	
Ambient pressure effects	<0.04% reading per 1% change ambient pressure	
Analog outputs	Isolated 4-20mA, user selectable over measurement range	
Relay Outputs	3 x SPCO contacts: 250Vac, 3A or 28Vdc, 1A Alarm 1, Alarm 2, Fault	
Ethernet Output	Diagnostics and measurement data, standard RJ45 connector Modbus TCP	
ENVIRONMENTAL DATA		
Operating temperature	41°F to 113°F (5°C to 45°C)	

Operating temperature	41°F to 113°F (5°C to 45°C)
Storage temperature	23°F to 122°F (-5°C to 50°C)
Relative humidity	10 to 90% RH, non-condensing
Operating altitude	-1,600ft to 13,000ft (-500 to 4000m)
Ingress protection	IP65

#### DEVICE SPECIFICATION

Size	8.3" (210mm) W x 7.9" (200mm) H x 4.2" (106mm) D
Weight	<5.5lbs (2.5kg)
Weight	<5.5lbs (2.5kg)

\*After first 48 hours of operation

Please note: This document was updated in August 2014. While every effort has been made to ensure accuracy, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards and guidelines. This document is not intended to form the basis of a contract.

AMERICAS BUSINESS CENTER Tel: +1 281 295 5800 Email: americas\_sales@servomex.con

ASIA PACIFIC BUSINESS CENTRE Tel: +86 (0)21 6489 7570 Email: asia\_sales@servomex.com EUROPEAN BUSINESS CENTRE Tel: +31 (0) 79 330 1580 Email: europe\_sales@servomex.con

INDIA BUSINESS CENTRE Tel: +91 22 3934 2700 Email: MEL sales@servomex.com MIDDLE EAST BUSINESS CENTRE Tel: +971 6552 8073 Email: MEI\_sales@servomex.com

#### SERVOMEX.COM

Servomex has a policy of constant product improvement and reserves the right to change specifications without notice. © Servomex Group Limited. 2014. A Spectris company. All rights reserved.

# SERVOMEX **%**